

PAT-NO: JP409186894A
DOCUMENT-IDENTIFIER: JP 09186894 A
TITLE: COLOR IMAGE PROCESSING METHOD AND DEVICE
PUBN-DATE: July 15, 1997

INVENTOR-INFORMATION:
NAME
MURAI, KAZUMASA
KOKATSU, HITOSHI

ASSIGNEE-INFORMATION:
NAME FUJI XEROX CO LTD COUNTRY N/A

APPL-NO: JP07342886

APPL-DATE: December 28, 1995

INT-CL (IPC): H04N001/60, G06T005/00 , H04N001/46

ABSTRACT:

PROBLEM TO BE SOLVED: To maintain the black rate of an original image in the case of converting a color signal between different coordinates.

SOLUTION: An equipment independent color signal on a representation color system coordinate is calculated from a color signal CiMiYiKi on 1st CMYK coordinates (S50). Then a maximum black amount of the color signal CiMiYiKi is calculated based on the color signal CiMiYiKi and the equipment independent color signal and a black rate (g) of the color signal CiMiYiKi is calculated based on the maximum black amount and a color signals K<SB>1</SB> (S54). The maximum black amount taken in a range of not revising the equipment independent color signal is calculated from the equipment independent color

signal (S56).

A color signal $K_{<SB>0</SB>}$ on 2nd CMYK coordinates is decided based on the maximum black amount and the black rate and a chrominance signal $C_{<SB>0</SB>}$ $M_{<SB>0</SB>}$ $Y_{<SB>0</SB>}$ on the CMYK coordinate is decided based on the equipment independent color signal and the color signal $K_{<SB>0</SB>}$.

COPYRIGHT: (C)1997,JPO